MAXIMUS

CLICK 55

INVICTUS

Technical Specification - Technische Spezifikationen - Spécifications techniques - Technische specificaties

Description - Beschreibung - Description - Omschrijving		Rigid core SPC with IXPE sound insulating underlay attached
Thickness - Gesamtdicke - Epaisseur - Dikte	EN ISO 24337	5mm SPC + 1mm IXPE sound backing
Wearlayer - Nutzschicht - Couche d'usure - Slijtlaag	EN ISO 24340	0.55 mm
Wearlayer PUR coating - Schutz vor Schmutz PUR - Traitement polyurethane - PUR slijtlaag behandeling		Scratchmaster® top layer
Locking System - Verschlusssystem - Système de verrouillage - Vergrendelingssysteem		Unilin / I4F Click technology
Weight per sqm - Flächengewicht g/m² - Poids total g/m² - Totaal gewicht g/m²	EN ISO 23997	ca. 9820 g/m²
Classification - Eignungsklasse - Classe d'usage - Gebruiksklasse	EN ISO 10874	33 Commercial Heavy - 42 Industrial General

Performance - Leistungen - Prestaties

Reaction to fire - Brandverhalten - Classement feu - Brandklasse	EN 13501-1	Bfl-S1
Slip resistance - Rutschfest - Glissance - Antislip	EN 13893	DS
Slip restraint (dynamic coefficient of friction) - Rutschhemmung - Résistance au glissement - Slipweerstand	DIN 51130	R10
Thermal resistance R value - Wärmedurchlasswiderstand R - Résistance thermique R - Wamtedoorlaatweerstand R	EN 12664	0.048 (m².K)/W
Thermal conductivity - Wärmeleitfähigkeit - Conductivité thermique - Warmtegeleiding	EN 12664	0.128 (W/m.K)
Underfloor heating - Bodenheizung - Chauffage par le sol - Vloerverwarming	EN ISO 12524	Yes, max. 27°C
Electrostatic performance - Antistatik - Accumulation de charges électrostatiques - Electrostatische propensiteit	EN 1815	< 2 kV
Residual indentation - Eindrückverhalten - Poinçonnement rémanent - Restindruk	EN ISO 24343-1	< 0.1 mm
Dimensional stability - Massänderung - Stabilité dimensionelle - Dimensionele stabiliteit	EN ISO 23999	≤ 0.15%
Curling - Schüsselung - Incurvation - Krulling	EN ISO 23999	pass
Castor chair resistance - Stuhlrollenfestigkeit - Résistance aux chaises à roulettes - Bestand tegen stoelwielen	EN ISO 4918	pass, Type W
Colour fastness - Farbechtheit - Solidité de la couleur - Kleurechtheid	EN ISO 105-B02	> 6
Impact sound insulation - Trittschallverbesserungsmaß - Efficacité acoustique - Kontaktgeluidisolatie	EN ISO 717-2	20dB (ΔLw)
Chemical / Stain resistance - Fleckenbeständigkeit - Résistance aux taches - Vlekbestendigheid	EN ISO 26987	pass
Abrasion resistance - Verschleißfestigkeit - Résistance à l'abrasion - Slijtvastheid	EN ISO 660-1	class T
Indoor AIR quality - French VOC regulation	ISO 16000	Greenguard GOLD - Floorscore - A+
Content of pentachlorophenol		PCP under detection limit
Formaldehyde emissions (28 days test)	EN ISO 717-1	NA HCHO (has not been added)
Phthalate free		Yes, biobased
CE marking	EN 14041:2011	

Packaging - Verpackung - Emballage - Verpakking

Size and packaging wood	EN ISO 24342	178x1213 mm	8 planks / carton = 1.725 m² / carton
Size and packaging wood XL planks	EN ISO 24342	235x1518 mm	4 planks / carton = 1.426 m² / carton
Size and packaging wood XL planks	EN ISO 24342	225x1500 mm	4 planks / carton = 1.350 m² / carton
Size and packaging stone	EN ISO 24342	298x603 mm	8 tiles / carton = 1.440 m² / carton
Size and packaging stone XL tiles	EN ISO 24342	450x907 mm	4 tiles / carton = 1.633 m² / carton

Warranty - Garantie

Warranty - Garantie	25 years Residential - 15 years Commercial

The technical data is correct at the time of printing.- 04/2023

scratchmaster® outperforming wear protection · 25 year warranty · 15 year commercial warranty · family friendly · pet friendly · water proof · easy maintenance · silent underfoot · underfloor heating · bevel · quick & easy · no subfloor preparation · 100% recyclable and reusable · PHTHALATE FREE

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ · eco+ PHTALATE FREE BIO BASED CONTENT · INDOOR AIR COMFORT eurofins GOLD CERTIFIED PRODUCT

invictus.eu